


Bella Neo



AGT Bella NEO laminate

Available in AC3/W31 - Square edge


Plank dimensions: 1200 x 191 x 8mm (2.292 sqm/box)

by

FINfloor™

www.finfloor.co.za

Bella Neo



SPECIFICATIONS	AC3/W31 - Square Edge
Top surface	Melamine impregnated decorative film. Protected by anti abrasive overlay.
Core material	H.D.F. (High Density Conifer Fibreboard) impregnated with wax treatment for greater water/moisture resistance. Average core density $\geq 860/880\text{kg/m}^2$
Bottom surface	Balancing film
Plank dimensions	1200 x 191 x 8mm
Installation method	Unilin L2C locking system (Glue-less Installation)
Warranty	15 years heavy residential 5 years moderate commercial use
Fit for use grading	AC3/W31 Heavy Residential AC3/W31 Moderate Commercial

TECHNICAL DATA	AC3/W31 - Square Edge	
TEST	STANDARD	CHARACTERISTICS/ RESULTS
Abrasion resistance	EN 438	> 2000 Revolutions
Surface soundness	EN 13329	$S > 1 \text{ N/mm}^2$
Scratch resistance	EN 438	> 3,5
UV resistance	EN ISO105	Level 6 - Blue wool scale (No discolouration)
Impact resistance	EN 13329	IC 1 for Class 31
Effect of a soft castor chair	EN 425	No change or damage on appearance should occur
Effect of soft castor furniture leg	EN 424	No visible damage should occur
Resistance to hot pots	EN 13329	Class 4
Resistance to cigarette burn	EN 13329	Class 4
Resistance to water vapour	EN 13329	Class 4
Fire classification	EN13501-1/EN14041:2004	Flame-retardant - B1
Stain resistance	EN 13329	Class 5
24 hour thickness swelling test	EN 13329	$\leq 18\%$ swelling
Density	EN 323	860-880 kg/m^2
Static locking strength (Joint strength)	ISO 24334	>590 KG/LM
Anti-bacterial	DIN EN ISO 20743	99.9% effective

